

MAXRON Ethernet Switch


MSW-3008F-P

- 8 ports 100Mbps
- 6KV Lightning & 8KV ESD Protection
- Compact Design, Competitive Solution


Specifications



Dimension (mm)



Installation Diagram



Model	MSW-3008F-P
Ports	(1~8):10/100Mbps ports (RJ45)
Transmission Rate	200Mbps Full Duplex; 10 or 100Mbps Half Duplex
Transmission Distance	100m
Performance Specification	Bandwidth:1.6Gbps
	Network Latency (10 to 100Mbps): $\leq 16\mu s$ (use the 64byte package size)
	MAC address table: 2K
	The Frame Filter & Transmission Rate: 14800pps the most for 10M port, 148800pps the most for 100M port;
Networking Standard	IEEE 802.3i 10BASE-T
	IEEE 802.3u 100BASE-TX
	IEEE 802.3x Flow Control
Power Support	Power Input: AC 90~264V 3W
Physical Specifications	Size(L*W*H): 138mm*70mm*25mm, Weight: 0.2KG
Working Environment	Operating Temperature: -30°C~60°C
	Storage Temperature: -40°C~70°C
	Operating Humidity: 10%~90% Non-condensing
	Storage Humidity: 5%~90% Non-condensing
Certification	CE Mark
	FCC Part15,Class B
	RoHS 2.0
Guarantee	25 months
Package Content	User Manual